

Bases de Datos

Para conectar a una base de datos necesitamos un driver, que es un fichero que debe estar en el path del proyecto en /WEB-INF/lib.

[context.xml](#)


```
<Context>
  <resource name="jdbc/dad2" auth="Container"
type="javax.sql.DataSource" <!--Name: TipoDeRecurso/NombreAsignado-->
maxActive="50" maxIdle ="30"maxWait="10000"
username="root" password=""
driverClassName="com.mysql.jdbc.Driver"
uri="jdbc:mysql://localhost:3306/dad"/>
</Context>
```

[Control.java](#)

```
public class Control extends HttpServlet{
    private static final long serialVersionUID = 1L;
    public static final String PRM_ACCION = "PRM_ACCION_CONTROL";

    private Hashtable<String, Accion> hashAcciones=null;
    private static Factory factory = null;

    public void init() throws ServletException{
        system.out.println("Iniciando...");
        PreparedStatement ps = null;
        resultSet rs = null;
        try{
            Connection con = Control.ds.getConnection();
        }catch{
        }
    }
}
```



From:
<http://www.knoppia.net/> - Knoppia

Permanent link:
<http://www.knoppia.net/doku.php?id=dad2:bbdd&rev=1712659575>

Last update: **2024/04/09 10:46**

